READ FOR RECORD

(E Pages)

#### ORDNANCE COMMITTEE ITEM 35517 23 SEP 54

DEPARTMENT OF THE ARMY Office of the Chief of Ordnance

A-306 A HRosenthal/sd/53401 24 July 1954

FROM:

Subcommittee on Ammunition

TO:

The Ordnance Technical Committee

SUBJECT: SHELL, CHEM, 155-MM, M121 (T77): CASING, BURSTER, M15 (T29E1), CHARGE, BURSTER, M37 (T69) - Classified as Standard Type

#### 1. REFERENCES:

- a. CCM Items 32335 dated 19 August 1948 and 32413 dated 14 October 1943, Subject: Improved Gas Shell (Shell, Chemical, 155-mm, T77) Initiation of Development.
- b. Test Division Chemical Corps, Chemical and Radiological Laboratories Final Engineering Report No. 14 on Shell, 155-mm, Howitzer, Gas, T77 Filled GB, dated 1 May 1952 (Project No. 4-04-15-012).
- c. Test Division Chemical Corps, Chemical and Radiological Laboratories, Supplement to Final Engineering Report No. 14 on Shell, 155-mm. Howitzer, Gas, T77, Filled GB, dated 21 November, 1952 (Project No. 4-04-15-012).
- d. Aberdeen Proving Ground Firing Record P-50359, 23 August to 29 September 1951: Range Firing of Shell, Chem, T77, 155-mm, Howitzer.
- e. Aberdeen Proving Ground Firing Record P-48812, 19 and 21 July 1951: Development of Shell, Chem, T77 155mm Howitzer, Recovery and Preliminary Range Firings.
  - f. Letter 00 471.16/6 to Chief, Army Field Forces dated 30 October 1951, Subject: Shell, Chemical, 155-mm, T77 (Project TA1-1754).
  - g. File 00 471/2596 (155-mm); G4/F3 31552 (25 April 1952); G3 470 (25 April 1952); ATDEV-10 471/651 (25 April 1952): GNBA-105 471 (FA 5151).
  - h. CCTC Item 1890 dated 19 May 1946.
  - i. SR 380-5-6 dated 18 June 1952.
  - j. Letter File 00 471.82/420 and CCM Item 34087.

#### S.E.C.R.E.T

#### Item 2933



- k. Aberdeen Proving Ground Firing Record No. P-42745.
- 1. CCM Item 34008 dated 6 December 1951.
- m. Subcommittee Report Y-295.
- n. CCM 34444 dated 9 October 1952, Subject: Security Policy for GB Filled Munitions.
- o. OCM Item 35212 dated 11 March 1954. Subject: Booster M125 (T23) - Classification as Substitute Standard Type and other items.
- p. SR 700-51-190 dated 4 June 1951.
- q. File 00 400/955 (S) (CML/R-C) from Chief Chemical Officer to Chief of Ordnance 24 August 1953, Subject: Standardization of Chemical Warfare Munitions.
- r. File AGAC-C (M) 381 TSS1 (27 Apr 53) G3, Subject: Chemical and Biological Warfare Readiness.
- s. File 00 471/2061 (misc) (S); CMLWX-T dated 2 October 1952; Subject: Adequacy of Press Fit closure in GB filled Artillery Shell.
- t. File 00 471/3049 (misc) from 000 to Ch. Chemical Officer dated 23 November 1953, Subject: Shell, Gas of the 105mm, T173 and 105mm, T173 and 155mm, T77 types.

#### 2. DISCUSSION:

- a. Development of Shell, Chemical, 155-mm, T77 was initiated and approved by reference la. In order to complete the development by the desired date, the T77 Shell for Engineering and Development Tests were produced by modification of Shell, Chem, 155-mm, M104 which were available. The modifications comprised:
  - (1) Removing the rotary band and rebanding with a rotating band similar to those used on the M107 and M110 Shell.
  - (2) Providing new nose adapters to fit the increased burster size required for properly disseminating the filler.
  - (3) Providing new and larger burster casings and burster charges.
- b. Initially a small number of shell with several sizes of burster casings and burster charges were manufactured and delivered to the Chemical Corps. These shell were filled by the Chemical Corps, and a series of tests were conducted at Army Chemical Center to establish a burster charge for the best dispersion of GB in an airborne cloud. Under the conditions of these tests a shell design with an agent burster ratio of 2 to 1 was selected as producing the best results. A supply of shell with this 2 to 1 ratio were produced. These shell were supplied the Chemical Corps for filling. A number of the shell were GB filled for tests by the Chemical Corps at their





### UNCLASSIFIED

#### Item 2933

Dugway Proving Ground, and the remainder were simulated filled (furfural) for firing at Aberdeen Proving Ground and at Army Field Forces Board No. 1.

c. Chemical Corps evaluation of the T77 (M121) Shell is reported in reference lb.. This report indicated satisfactory results in all phases except the corrosion test on which the report stated:

"Corrosion tests not yet completed, results will be reported in a supplement to this report. Only one shell (No. 289) of all those used in the test program was found to leak. This leak was definitely due to a burster well fabrication defect which was caused by an improper solder seal between the burster well body and closure plug."

Reference 1b recommended:

"On the basis of the test phases completed, the Shell, 155-mm, Howitzer, Gas, T77, Filled CB, is satisfactory in regards to all military characteristics with the exception of the corrosion tests."

d. Reference lc supplements reference lb subsequent to completion of Chemical Corps cyclic surveillance of Shell, GB, 155-mm, T77. This report stated:

"The projectile allowed no leakage during extended periods of simulated climatic storage, and showed no evidence of corresion by the agent for which it is designed, after such storage."

The recommendations were as follows:

"On the basis of test results incorporated in basic Final Engineering Report No. 14, dated 1 May 1952, as supplemented by surveillance data outlined herein, it is recommended that Shell, 155-mm, Howitzer, Gas, T77 (Filled GB), as submitted, be considered satisfactory as regards filling the stated military requirement and meeting the stated military characteristics." Later correspondence between Chief Ordnance and Chief Chemical Office, reference 1t, indicated that some difficulties might be expected from leaks at silver soldered joints.

e. Results of Aberdeen Proving Ground are reported in references 1d and le. The Aberdeen tests included range and accuracy tests in comparison with Shell, HE, 155-mm, M107 as well as excess pressure tests and sympathetic propagation tests. The range and accuracy tests indicated that Firing Table 155-2-2, with a correction for 1½% increase air density is applicable when firing the T77 Shell. That is, the Shell T77 may be fired using FT 155-2-2 for the weight zone marked on the shell, but the range will be shorter than that of a HE Shell, M107 in the same weight zone by an amount equal to the effect of an increase of 1½% in air density. The excess pressure tests indicated that the burster could be expected to safely withstand the maximum pressure in the M1 Howitzer. The propagation tests indicated that Shell T77 assembled with Burster Charge T69 and stored in piles would not propagate sympathetically if one of the shell in the pile was detonated. On the recovery test, examination of the recovered rounds

revealed that there was no deformation, or separation of metal parts on any round.

- f. Shipment of 149 Shell, Chemical, 155-mm T77 furfural loaded was made to Army Field Forces Board No. 1. Reference If covered this shipment. Information on the density and weight zone corrections indicated in paragraph 2e above was supplied to Army Field Forces, and the opinion of Army Field Forces was asked whether or not firing tables would be needed for firing the T77 Shell. Army Field Forces Board No. 1 conducted tests on the Shell, Chemical, 155-mm, T77 and their report is covered in reference lg. This report recommended:
  - "a. Shell, Chemical, 155-mm, T77 be considered suitable for Field artillery use with regards to accuracy and stability."
  - "b. Firing Table 155-1-2 be considered suitable for use with Shell, Chemical, 155-mm, T77."
- g. Construction of the items to be standardized is shown on the following drawings:
  - (1) Shell, Chem, 155-mm, Ml21 (T77) P-82762, P-82763 (75-4-199, 75-4-200).
  - (2) Casing, Burster, M15 (T29E1) P-926119 (73-1-247.) (being prepared)
  - (3) Charge, Burster, M37 (T69) P-82764 (73-1-246.)

It is expected that a number of engineering changes will be made on those drawings (excluding the fuze) both to facilitate production from new forgings instead of from modification of existing shell, and to eliminate one or more silver solder joints similar to the joint cited in paragraph 2c above.

- h. It is desirable to specify one piece construction for the shell body (less fuze adapter) and one piece construction for the burster casing in order to eliminate the possibility of leaks thru silver soldered joints. Current production of 20000 of the T77 (M121) shell bodies is with a body adapter silver soldered to the shell body. On future production every effort will be made to eliminate any shell body joint in the chemical cavity.
- i. The present drawings for Casing, Burster, shows both a two piece design closed with a plug silver soldered to the bottom of the tubing, (T29) and also a one piece design to be made by cold forming (T29E1). The latter design is in manufacture for the current production of 20000 shell cited in paragraph 2h above. It is intended to eliminate the two piece design from the drawing and make the one piece design mandatory.
- j. GB was standardized by reference lh. Paragraph 3c of this reference recommended that:






"GB itself be classified as a RESTRICTED item, that the symbol GB, when used alone be UNCLASSIFIED; etc."

This recommendation was approved by higher authority. An UNCLASSIFIED category for the filled T77 Shell would meet the requirements quoted above as the GB itself would be under cover, hermetically sealed within the shell body.

- k. Reference li in paragraph 2h classifies as SECRET munitions developed, or under development, for dissemination of the nerve gases until such time as munitions are standardized for operation use and issue. When munitions are standardized for operation use and issue, the appropriate classification for such will be designated by the agency having prime cognizance in accordance with applicable current directives of higher authority.
- l. All ballistic tests of the T77 Shell were conducted with Fuze, PD, M51 (Series) since a more satisfactory fuze was not available at the time. The Chemical Corps indicated that somewhat better terminal ballistics could be expected with a faster operating fuze. Consequently the mechanical Fuze, PD, T237El and the electrical Fuze, PD, T244 have been under development under authority of reference lj for use on all rotated GB shell. The T244 Fuze which will be an optimum type to include minimum functioning time and graze sensitivity is still in the preliminary stages of development.
- m. Reference lo is a special regulation covering Logistic Responsibility for Standard Commodity Classification, Major Group 90, Ordnance. This regulation assigns responsibility of toxic ammunition for rifled weapons as follows:
  - (1) Ordnance Corps: Specifications, requirements and funds, purchase and inspection, storage and issue, and maintenance of the complete round and requirements and funds for the filler.
  - (2) Chemical Corps: Specifications, purchase and inspection, storage and issue, and maintenance of the filler.
- n. Subcommittee Report A-306 was originally submitted to the Ordnance Technical Committee in October 1952. Internal Ordnance Corps, non-concurrences were submitted due to possibility of "leakers" at the closure, both in assembly and storage. Procurement of 20000 each, T77 was undertaken, and joint surveillance tests on these 20000 shell filled GB, was arranged between the Ordnance Corps and the Chemical, see reference lr. The withdrawal of the internal Ordnance Corps non-concurrences was to depend upon the successful conclusion of these tests. These tests have not yet been instituted.
- o. By reference lq the Chief Chemical Officer recommended to the Chief of Ordnance to immediately standardize the currently released CB ground munitions utilizing press fit closures. The following is quoted from this reference "---The Chemical Corps---has designed, investigated, studied and tested some thirty (30) different designs of closures. None have been found to excel the current design press fit closure. Approximately seven thousand (7000) press fit closures have been accomplished by this Corps



#### Item 2933

in the past two years without detecting a single closure leak. This record was attained by careful inspection of metal parts by capable inspectors."

"Hositancy to standardize these munitions and confusion relative to closures are due to fear of physical contact with agent GB. This agent is a more hazardous material than most; however, the Chemical Corps has developed adequate detection and protection devices---!

p. By 1st Ind to reference 1q Ordnance corps advised the Chemical Corps

"The Ordnance Corps is taking action to effect standardization of the 105mm and 155mm Howitzer GB Shells with the present closure design. The internal Ordnance non-concurrences to such action have been withdrawn."

- q. The following information is pertinent to standardization of Shell, Chemical, 155-mm, Ml21 (T77) with Casing, Burster, Ml5 (T29); Charge, Burster, M37 (T69): with GB filling, but without fuze or propelling charges, both of which are separate items of issue.
  - (1) Proposed using agencies: Army Field Forces, National Guard Bureau, and U. S. Marine Corps.
  - (2) Related material: Howitzer, 155-mm, Ml: Charge, Propolling, M3 and M4Al; Fuze, FD, T237El; Primer, M2A4.
  - (3) No existing items need to be modified or replaced by the GB filled Shell, 155-mm, M121 (T77).
  - (4) The filled, assembled and fuzed shell will cost approximately \$51 each in production quantities.
  - (5) The item meets current military characteristics for GB filled, non-persistent gas shell for the 155-mm, Howitzer, MI except for possibly occasional "leakers" as indicated in paragraph 2c above.
  - (6) The item is intended for immediate procurement.
  - (7) Critical or strategic material used (exclusive of filler which is a standardized Chemical Corps item): Gilding metal of rotating bands and small quantities of brass and aluminum in the fuze.
  - (8) Item is air transportable.
  - (9) The Ordnance Corps is to be charged with responsibility for:
    - (a) Specification for the round (including all components except filler).
    - (b) Purchase and inspection of all parts, except filler.





## UNCLASSIFIED

#### Item 2933

- (c) Determination of requirements and funding.
- (d) Assembly of the filled shall.
- (e) Storage and issue of the filled and assembled shell.
- (f) Maintenance of the filled and assembled shell.
  The Chemical Corps is to be charged with responsibility for:
- (g) Specifications for the filler.
- (h) Purchase and inspection of the filler and the filling.
- (i) Storage and issue of the filler.
- (j) Maintenance of the filler.
- r. Since Shell, Chem, 155-mm, Ml21 (T77) with Fuze, PD, T237El, and Casing, Burster, Ml5 (T29El); Charge, Burster, M37 (T69) with 3B Filling covers a requirement for which there is at present no existing standard projectile, it is the opinion of the Subcommittee that it should be authorized as standard. It is also the opinion of the Subcommittee that development be continued in order to reduce the possibility of "leakers" and to obtain the fastest practical fuze functioning by electrical or mechanical means. Improvement of closure will be continued as a portion of Project TA1-1546 (D/A 504-04-004) in connection with development of Shell, Chemical, 105-mm, T302. Development of the faster electric fuze will be continued as a portion of Project TA1-2706 (D/A 505-02-023).
- s. Funds for procurement of 177,794 fuzed Shell, Chem. 155-mm, T77 (GB filled) were authorized by references 11 and 1m. This authorization was subsequently reduced to 20,000 rounds. On 14 June 1954, the Chief of Staff approved a revision of reference 1r. The revised directive eliminates the stockpile concept of chemical munitions and directs computations on an MRMR basis as of 1 July 1954. Funds for the procurement of the round will be required to meet the computed MRMR. Funds to procure 60,000 rounds have been approved by G4 and will be made available to Industrial Division.

#### 3. RECOMMENDATIONS:

The Subcommittee recommends that:

- a. Shell, Chemical, 155-mm, Ml21 (T77); Casing, Burster, Ml5 (T29E1); Charge, Burster, M37 (T69); be classified as Standard Types.
- b. The filled shell be designated "Shell, Gas, GB, Non-Persistent, 155-mm, M121 (T77)."
- c. Firing Table 155-Q-2 be revised to include Shell, Gas, GB, Non-Persistent, 155-mm, M121 (T77).

# S.E.C.B.E.T

Item 2933



- d. Improvement in method of closure be continued as a portion of Proj. Tal 1546 (D/A 504-04-004).
- e. The security classification of Shell, Gas, Non-persistent (GB), 155-mm, Ml2l (T77) together with its component parts, drawings, and specifications be UNCLASSIFIED except that complete details of the methods of manufacture of GB is classified SECRET; its chemical composition is UNCLASSIFIED, the methods of handling, antidotes and physiological effects of the filler are UNCLASSIFIED. Also, the amount of stocks of Ml2l shell available or about to become available should be classified CONFIDENTIAL. Correspondence concerning stocks of Ml2l ammunition may be CONFIDENTIAL, or UNCLASSIFIED at the discretion of the originating office in accordance with the subject of the communication, provided such communication does not reveal information leading to the quantities available for use.
  - f. This report be placed in the Secret category.
- g. Logistic responsibilities are to be as assigned in SR 700-51-190 dated 4 June 1951 (this SR is currently under review).

	•	
	J. B. ÆDARIS Brig Gen, USA	JOHN G. ZERDT Col, Ord Corns
RENCE W. BYERS , GS FF	F. B. BRYAN Col, Ord Corps	S. A. HALL Col, Ord Corps
		el •
H. CLARK , Ord Corps	JOHN KELIER Lt Col, Ord Corps National Guard Bureau	H. H. EVANS Lt Col, USMC
W. STOREY	W. J. WISEMAN Jr.	H. G. ADAMS
W. STOREY	W. J. WISEMAN Jr.	H. G. A

Chemical Coros

ORD Corps
Action By:

Amm Br, Ord Res & Dev Div.
Res & Mats Br, Ord Res Dev Div.
Amm Br, Industrial Division.
Amm Supply Br, Field Service Div.
Requirements Br, Field Service Div.

Approval by higher authority is required.

APPROVED BY ORDNANCE COMMITTEE

23 SEP 54

/S/ A. W. STCDDARD Col, Ord Corps Secretary APPROVED
/S/ M. H. CLARK
Col, Ord Corps
Chairman Pro Tem

Lt Col, Ord Corps

APPROVED BY ORDER OF THE SECRETARY OF THE ARMY

/S/ GARRARD FCSTER, Lt Col. GS
For the Denuty Clief of Staff for
Logistic

/S/ GA For the

# NCI ASSIFIE

Item 2934

(8 Pages)



#### ORDNANCE COMMITTEE ITEM 35518

23 SEP 54

A-512 HRosenthal/sd/53401 . 9 August 1954

DEPARTMENT OF THE ARMY Office of the Chief of Ordnance

FROM:

Subcommittee on Ammunition

TO:

The Ordnance Technical Committee

SUBJECT:

Shell, Chem., 155-mm, M122 (T179); Casing, Burster, M17 (T32)

Classified as Standard Type.

#### 1. REFERENCES:

- COM Item 33567 dated 5 February 1951, Subject: Shell, Chemical, 105-mm, T173 Shell, Chemical, 155-mm, T179 Shell, Chemical, 8-inch, T174 Initiation of Development
- b. Test Division Chemical Corps, Chemical and Radiological Laboratories, Final Engineering Report No. 14 on Shell, 155-mm, Howitzer, Gas, T77, Filled GB, dated 1 May 1952 (Project No. 4-04-15-012)
- c. Test Division Chemical Corps, Chemical and Radiological Laboratories, Supplement to Final Engineering Report No. 14 on Shell, 155-mm, Howitzer, Gas, T77, Filled GB, dated 21 November, 1952 (Project No. 4-04-15-012)
- d. Aberdeen Proving Ground Firing Record P50359, 23 August to 29 September, 1951: Range Firing of Shell, Chem, T77, 155mm, Howitzer.
- e. Aberdeen Proving Ground Firing Record P-50774, 27 February 1952: To determine dimensional stability of Shell, Chemical, T179, for 155MM Gun, and satisfactoriness of components at 112% maximum rated gun pressure.
- f. Aberdeen Proving Ground Firing Record P-51481, 1 May 1952, 13 June 1952: To determine if Shell, Chemical, T179, for 155mm Gun can be Fired Using the Range Table for the M101 Shell, with Suitable Weight Zone Correction.
- g. Aberdeen Proving Ground Firin- Record P-59204, 13 and 20 April, 1954; Birster for Shell Chem 155mm T179.



- h. D/F 00471/255 (155mm), (G3 470 (6 Jan. 53)) dated 23 January 1953, Subject: Shell, Chemical, 155mm, T179 and inclosing letter ATDEV 10 471/1 (5 Jan 53) with letter GNBA FAG 471 (FA 3452) from Headquarters AFF Board No. 1 dated 11 December 1952.
- i. CCTC Item 1890 dated 19 May 1946.
- j. SR 380-5-6 dated 18 June 1952.
- k. OCM Item 34444 dated 9 October, 1952 Subject: Security Policy for GP Filled Munitions.
- 1. SR 700-51-190 dated 4 June 1951.
- m. File 00 400/955 (s) (CMLWR-C) from Chief Chemical Officer to Chief of Ordnanco, 24 August 1953, Subject:
  Standardization of Chemical Terfare Munitions.
- n. File AGAC-C (M) 381 TSSI (27 April 53) G3, Subject: Chemical and Biological Warfare Readiness.
- o. File 00 471/2061 (Misc)(S), CMLWX-T dated 20 October 1952, Subject: Adequacy of Press Fit Closure in GB filled Artillery Ammunition,
- p. File 00 471/3049 (misc) from CCO to Chief Chemical Officer dated 23 November 1953, Subject: Shell, Gas of the 105mm, T173 and 155mm, T77 Types.
- q. Subcommittee Report A-306A dated 24 July 1954 Subject: Shell, Chem, 155-mm, M121 (T77); Casing Burster, M15 (T29E1); Charge, Burster, M37 - Classified as Standard Type.
- r. Letter File 00471.82/420 and 00M item 34087.

#### 2. DISCUSSION

- a. Development of Shell, Chemical, 155-mm, T179 was initiated and approved by reference la. In order to complete the development by the desired date, the T179 Shell for Engineering and Development Tests were produced by modification of Shell, Chem, 155-mm, M104 which were available. The modifications comprised:
  - (1) Providing new nose adapters to fit the increased burster size required for properly disseminating the filler.
  - (2) Providing new and larger burster casings and burster charges.
- b. Shell, Chemical, 155-mm, TL79 as produced for development and engineering tests was identical with Shell, Chemical, 155-mm, T77 except for the rotating band. Therefore all evaluation by the Chemical Corps for tests required by them were conducted on the T77 shell. These tests included selection of burster ratio, evaluation of filler dissemination by









### INCLASSIFIED

#### Item 2934

actual firing tests, and accelerated surveillance tests, none of which would be affected by the design of the rotating band.

c. Chemical Corps evaluation of the T77 Shell is reported in reference lb. This report indicated satisfactory results in all phases except the corrosion test on which the report stated:

"Corrosion tests not yet completed, results will be reported in a supplement to this report. Only one shell (No. 289) of all those used in the test program was found to leak. This leak was definitely due to a burster well fabrication defect which was caused by an improper solder seal between the burster well body and closure plug."

#### Reference 1b recommended:

"On the basis of the test phases completed, the Shell, 155-mm, Howitzer, Gas, T77, Filled GB, is satisfactory in regards to all military characteristics with the exception of the corrosion tests."

d. Reference lc supplements reference lb subsequent to completion of Chemical Corps cyclic surveillance of Shell, GB, 155-mm, T77. This report stated:-

"The projectile allowed no leakage during extended periods of simulated climatic storage, and showed no evidence of corrosion by the agent for which it is designed, after such storage."


The recommendations were as follows:

"On the basis of test results incorporated in basic Final Engineering Report No. 14, dated 1 May 1952, as supplemented by surveillance data outlined herein, it is recommended that Shell, 155-mm, Howitzer, Gas, T77 (Filled GB), as submitted, be considered satisfactory as regards filling the stated military requirements and meeting stated military characteristics."

Later correspondence between Chief of Ordnance and Chief Chemical Officer (reference lp.) indicated that some difficulties might be expected from leaks at silver soldered joints.

e. Results of Aberdeen Proving Ground tests are reported in references ld to lg incl. The Aberdeen tests included range and accuracy tests in comparison with Shell, HE, 155-mm, M101, as well as excess pressure tests and sympathetic propogation tests. The latter test was conducted in with Shell, Chem, 155-mm, T77 which is the same as the T179 shell except for the size of the rotating band. The range and accuracy tests indicated that Shell, Chemical, T179 for 155-mm Gun, can be fired using the range table for the M101 shell, with suitable weight zone correction. The excess pressure test on five shell fired for recovery and measured before and after firing resulted in a maximum increase in diameter of shell of .002" during the firing. This firing was conducted with inert loaded











#### Item 2934

bursters and inert fuzes. An examination of the shell after firing indicated excessive set back of the burster material and some deformation of the burster casing. This test was later repeated using T77 shell, a one piece burster casing, and four different burster loadings. These loadings were, inert material, cast tetrytol, and pressed tetryl pressed at two loading pressures. These were fired with inert fuzes. The results of this test indicated that:

- (1) The live bursters were in better condition after firing than the inert bursters.
  - (2) The pressed tetryl bursters, which were compressed to 20,000 psi and 15,000 psi, were broken up but not separated as were the inert bursters and the tetrytol bursters.
  - (3) All tetrytol bursters of the same lot which were fired with live fuzes, functioned satisfactorily in spite of the fact voids were produced in the burster after firing.

The propagation test indicated that the shell assembled with Burster Charge T69 and stored in piles would not propogate sympathetically if one of the shell in the pile was detonated.

- f. Shipment of a lot of Shell, Chemical, 155-mm, T179 furfural loaded was made to Army Field Forces Board No. 1, who conducted tests on these shell. Their report is covered in reference lh. This report recommended:
  - "a. Shell, Chemical, 155-mm, T179, is suitable for field artillery use with regard to accuracy and stability."
  - "b. Firing Table 155-S-2 is suitable for use with Shell, Chemical, 155-mm, Tl79".
  - g. Construction of the shell as fired on the engineering and Service Board tests is shown on the following drawings:
    - (1) Shell, Chem, 155-mm, Tl79- Loading Assembly, P-93380 dated 15 February 52.
    - (2) Shell, Chem, 155-mm, T179- Metal Parts Details, P83382 dated 15 February 1952.
    - (3) Shell, Chem, 155-mm, Tl79 Metal Parts Assembly, P-83381 dated 15 February 1952.

These drawings show multiplece construction for both the shell body and the burster casing. It is desirable to eliminate the silver solder joints on both of these pieces in order to minimize possible leaks at such joints similar to the joint cited in paragraph 2c above. Therefore, the drawings have been revised to eliminate all silver solder joints and construction of the items to be standardized is shown on the following drawings:







#### Item 2934

- (2) Casing, Burster, M17 (T32) P-85511 rev. 3-11-54
- h. GB was standardized by reference li. Paragraph 3c of this reference recommended that:

"GB itself be classified as a RESTRICTED item, that the symbol GB, when used alone be UNCLASSIFIED; etc."

This recommendation was approved by higher authority. An UNCLASSIFIED category for the filled T179 Shell would meet the requirements quoted above as the GB itself would be under cover, hermetically sealed within the shell body.

- i. Reference lj in paragraph 2h classifies as SECRET munitions developed, or under development, for dissemination of the nerve gases until such time as munitions are standardized for operational use and issue. When munitions are standardized for operation use and issue, the appropriate classification for such will be designated by the agency having prime cognizance in accordance with applicable current directives of higher authority.
- j. All ballistic tests of the T77 Shell were conducted with Fuze, FD, M51 (Series) since a more satisfactory fuze was not available at the time. The Chemical Corps indicated that somewhat better terminal ballistics could be expected with a faster operating fuze. Consequently the mechanical Fuze, FD, T237El and the electrical Fuze, FD, T244 have been under development under authority of reference lr for use on all rotated GB Shell. Development of the T237El Fuze has been completed, and the item released for procurement with rotated GB Shell. The T244 Fuze which will be an optimum type to include minimum functioning time and graze sensitivity is still in the preliminary stages of development.
- k. Reference <u>ll</u> is a special regulation covering Logistic Responsibility for Standard Commodity Classification, Major Group 90, Ordnance. This regulation assigns responsibility of toxic ammunition for rifled weapons as follows:
  - (1) Ordnance Corps: Specifications, requirements and funds, purchase and inspection, storage and issue, and maintenance of the complete round and requirements and funds for the filler.
  - (2) Chemical Corps: Specifications, purchase and inspection, storage and issue, and maintenance of the filler.
- 1. Reference lq was initially submitted to the Ordnance Technical Committee in October 1952. Internal Ordnance Corps non-concurrences were submitted due to possibility of "leakers" at the press fit closure, both in assembly and storage. Procurement of 20000 each T77 was undertaken, and joint surveillance tests on these 20,000 shell, filled GB, was arranged between the Ordnance Corps and the Chemical Corps. See ref lo. The withdrawal of the internal Ordnance Corps non-concurrences was to depend upon







the successful conclusion of these tests. These tests have not yet been instituted.

m. By reference lm the Chief Chemical Officer recommended to the Chief of Ordnance to immediately standardize the currently released GB ground munitions utilizing press fit closures. The following is quoted from this reference.

"---- The Chemical Corps---- had designed, investigated, studied and tested some thirty (30) different designs of closures. Mone have been found to excel the current design press fit closure. Approximately seven thousand (7,000) press fit closures have been accomplished by this Corps in the past two years without detecting a single closure leak. This record was attained by careful inspection of metal parts by capable inspectors."

"Hesitancy to standardize these munitions and confusion relative to closures are due to fear of physical contact with agent GB. This agent is a more hazardous material than most; however, the Chemical Corps had developed adequate detection and protection devices----."

- n. By 1st indorsement to ref. lm, Ordnance Corps advised the Chemical Corps "The Ordnance Corps is taking action to effect standardization of the 105mm, and 155mm Howitzer GP Shell with the present closure design. The internal Ordnance non-concurrences to such action have been withdrawn."
- o. The following information is pertinent to standardization of Shell, Chemical, 155-mm, M172 (T179) with Casing, Burster, M17 (T32); Charge, Burster, M37 (T69); with GB filling, but without fuze or propelling charges, both of which are separate items of issue:
  - (1) Proposed using agencies: Army Field Forces, Mational Guard Bureau, and U. S. Marine Corps.
  - (2) Related material: Gun, 155-mm, M2, Charge, Propelling, M19 Fuze, PD, T237El; Primer, M2A4.
  - (3) No existing items need to be modified or replaced by the GB filled Shell, 155-mm, Ml22 (T179).
  - (4) The filled, assembled and fuzed shell will cost approximately \$51 each in production quantities.
  - (5) The item meets current military characteristics for GB filled, non-persistent gas shell for the 155-mm, Gun, M2 except for possibly occasional "leakers" as indicated in paragraph 2c above.
  - (6) The item is intended for immediate procurement.
  - (7) Item is air transportable.





# SECRET UNCLASSIFILE

#### Item 2934

- (8) The Ordnance Corps is to be charged with responsibility for:
  - (a) Specifications for the round (including all components except filler).
  - (b) Purchase and inspection of all parts, except filler.
    - (c) Determination of requirements and funding.
    - (d) Assembly of the filled shell.
    - (e) Storage and issue of the filled and assembled shell.
    - (f) Maintenance of the filled and assembled shell.
      The Chemical Corps is to be charged with responsibility for:
    - (g) Specifications for the filler.
    - (h) Purchase and inspection of the filler and the filling.
  - (i) Storage and issue of the filler.
  - (j) Maintenance of the filler.
- (9) Training and maintenance literature is required.
- (10) This item is in Supply Class V for issue.
- p. Since Shell, Chem, 155-mm, M122 (T179) with Casing Burster, M17 (T32) with GB Filling covers a requirement for which there is at present no existing standard projectile, it is the obinion of the Subcommittee that development be continued in order to reduce the possibility of "leakers" and to obtain the fastest practical fuze functioning by electrical or mechanical means. Reference lq. recommends that development be continued on improvement of closures under Project TA1-1546 (D/A 504-04-004) and a faster fuze under Project TA1-2706 (D/A 505-04-023). Approval of this subcommittee report is not intended to modify the recommendations of Ref. lq as concerns development of improved closures or development of a faster fuze.
- q. On 14 June 1954, the Chief of Staff approved a revision of reference ln. The revised directive eliminates the stockpile concept of chemical munitions and directs computations on an MRMR basis as of 1 July 1954. Funding for the procurement of the round is being held in suspense pending resolution of the responsibility between Ordnance and Chemical Corps for the storage and issue of the complete filled round. Standardization at this time will allow the program to be implemented at the earliest possible date after decision.

#### 3. RECOMMENDATIONS:

The Subcommittee recommends that:

## UNCLASSIFIED

### SECHER



a. Shell, Chemical, 155-mm, M122 (T179) and Casing, Burster, M17 (T32) be classified as Standard Types.

b. The filled shell be designated "Shell, Gas, GB, Non-Persistent, 155-mm, M122 (T179)."

c. Charge, Burster, M37 (T69) be authorized for use with the M122 shell.

d. Firing Table, FT 155-S-2 be revised to include Shell, Gas, GB, Non-Persistent, 155-mm, M122 (T179).

e. The security classification of Shell, Gas, Non-persistent (GB), 155-mm, M122 (T179) together with its component parts, drawings, and specifications be UNCLASSIFIED except that complete details of the methods of manufacture of GB is classified SECRET: its chemical composition is UNCLASSIFIED, the methods of handling, antidotes, and physiological effects of the filler are UNCLASSIFIED. Also, the amount of stocks of M122 shell available or about to become available should be classified CONFIDENTIAL. Correspondence concerning stocks of M122 munitions may be CONFIDENTIAL, or UNCLASSIFIED at the discretion of the originating office in accordance with the subject of the communication, provided such communication does not reveal information leading to quantities available for use.

f. This report be placed in the SECRET category.

g. Logistic responsibilities are to be as assigned in SR 700-51-190 dated 4 June 1951 (this SR is currently under review).

Maj Gen, USA	Brig Gen, USA	
	F. G. ERYAN Col, Ord Corps	S. A. HALL Col, Ord Corps
M. H. CLARK Col, Ord Corps	JOHN MELLER Lt Col, Ord Corps Nat'l Guard Bureau	H. H. EVANS Lt Col, USMC
W.W. STOREY Ord Corps	W. J. WISEMAN Jr. Chemical Corps	H. G. ADAMS Lt Col, Ord Corps

Action By: Amm Br, Ord Res & Dev Div.

Res & Mats Br, Ord Res & Dev Div.

Amm Br, Industrial Division

Amm Supply Br, Field Service Div.

Requirements Br, Field Service Div.

Approval by higher authority is required.

APPROVED BY ORDNANCE COMMITTEE 23 SEP 54

/S/ A. W. STODDARD, Col, Ord Corps

Secretary

Col, Ord Corps Chairman Pro Tem APPROVED BY ORDER OF

APPROVED BY ORDER OF THE SECRETARY OF THE ARMY


A > PROVED

/S/ M. H. CLARK

/S/ GARRARD FOSTER, Lt Col, GS
For the Debuty Chief of Staff for Logistics









READ FOR RECORD
Copy No.
(5 Pages)

DEPARTMENT OF THE ARMY
OFFICE OF THE CHIEF CHEMICAL OFFICER
Chemical Corps Technical Committee
Army Chemical Center, Maryland

CMLWH

19 November 1954

MEMORANDUM FOR RECORD

SUBJECT: Air Force Project 5064, BW-CW Warheads for B-62 (S)

The attached data sheet for rewritten ARDC Project 5064, same subject as above, is reproduced herewith as information pertinent to related Chemical Corps research and development.

FOR THE CHAIRMAN, CHEMICAL CORPS TECHNICAL COMMITTEE:

7. S. Ecker

Incl
Data Sheet
Project 5064

T. S. ECKERT Secy, CCTC

Rewritten Rev

#### Project Data Sheet

PROJECT TITLE: EW-CW Warheads for B-62 (S)

SECURITY CLASSIFICATION: Top Secret 2.

3. PROJECT NUMBER: 5064

REPORT DATE: 10 February 1954

BASIC FIELD OR SUBJECT: Strategic Air Development, B-62 6.

7. SUB FIELD OR SUBJECT: Chemical, Biological and Radiological Weapons

7a. TECHNICAL OBJECTIVE: SA-11 - BW-3 - CW-3

COGNIZANT AGENCY: ARDC

DIRECTING AGENCY: WADC, Armament Laboratory

10. REQUESTING AGENCY: Hq, USAF

11. PARTICIPATION AND/OR COORDINATION: Dept. of the Army, Chemical Corps (P); Dept. of the Navy, Bu Aer, Bu Ord. (I)

Army Chemical Corps, Northrup Aviation 12. CONTRACTOR AND/OR LABORATORY: Inc.

13. RELATED PROJECTS: a. Essential - 103A-B62 b. Related - None

14. DATE APPROVED: 22 February 1946

15. PRIORITY: 1-A

17. ESTIMATED COMPLETION DATES: Dev - July 1958 Test - July 1959

18. FISCAL ESTIMATES: 51-53 6.0; 54 - 2.0; 55 - 15.0; 57 - 13.0; 58-59 15.0; T - 66.0

This project supersedes Project RDO-R-448-47 in 19. SUPERSEDED PROJECTS: part.

20. REQUIREMENT AND/OR JUSTIFICATION: This project will provide the B-62 missile with a BW-CW capability as expressed in the Statements of Military Characteristics for the Snark missile, dated 5 June 1951 from Headquarters USAF (See Item la). The authority for this project is contained in a letter (classification Secret) from Deputy Chief of Staff for Development, Hq, USAF, to Commanding General, Air Research and Development Command, Subject (Confidential) "USAF Guided Missile Warheads and Fuzes (Chemical Corps) dated 22 March 1951. (Secret)

21. BRIEF OF PROJECT AND OBJECTIVE: a. Brief. - The performance requirements as stated in the Military Characteristics for the BW Warhead require that the BW Warhead should be capable of:

(1) Effectively dispersing BW munitions in a uniform pattern over areas of various size determined by the warhead opening altitudes.

(2) Achieving reproducible ballistics.

(3) All weather employment.

The performance requirements as stated in the Military Characteristics for the CW Warhead state that the warhead should be capable of:

(1) Establishing a uniform concentration of GB vapor over an area of approximately 2,700,000 square feet. This concentration shall extend from the surface to a height of 6 1/2 feet and shall be lethal to a man at rest within 30 seconds.







- (2) Achieving reproducible ballistics.
- (3) All weather employment. (Seret) b. Approach. - It is presently planned to achieve the objectives mentioned in Box 21a above by the use of a large number of small CW and BW unit munitions clustered within the missile warhead compartment. It is necessary for efficient agent utilization (either BW or CW), that a nearly uniform casualty - producing concentration of agent be effected by the Warhead. It will therefore be necessary to develop a method of separating and dispersing the unit munitions from the warhead that will insure an effective and reproducible unit munition ground pattern. Several separation and dispersion systems are being examined but due to the lack of applicable data on unit munition separation and dispersion from supersonic missiles, no definite system has been established. The warhead designed is also being retarded due to the fact that the method of delivering the warhead to the proper position over the target has not been defined. At present it is not known whether the missile will be flown intact to this point or whether the warhead will be separated and follow a ballistic trajectory to the point of opening.

After the above mentioned problems have been resolved a preliminary warhead design will be established. It is expected that the design will consist of:

(1) A cluster adapter (loaded weight 7000 lb.).

(2) CW or BW unit munitions as applicable.

- (3) A suitable arming and fuzing system.
- (4) Means of achieving unit munition spearation and dispersion. This design will be subjected to the usual static tests. It will be dynamically tested using a fin stabilized test vehicle which will duplicate the terminal trajectory and velocity of the B-62 missile. From the results of these tests a prototype design will be established. Terminal ballistics, dispersion characteristics of unit munitions (inert) and complete warhead functioning will be determined, again using the fin stabilized test vehicle. These tests will have to satisfy the requirements of all engineering testing due to the following:

(1) No facilities exist or are planned where a warhead of this size can be tested using live agent.

(2) No facilities exist or are planned where the B-62 missile can be impacted, with live or inert unit munitions, and the results recorded. (Secret)


c. Tasks.

Task No. 1 - 50200 (Conf) CW Warhead for B-62

Contractor: Dept. of the Army, Chemical Corps,
Northrup Aviation Inc.

Object and Nature of Task: The object of this task
is to develop a CW (GB) warhead for the B-62 missile.
The warhead will consist of a 7000 lb. cluster of
small component GB bombs which cluster will airburst
and provide random distribution of component bombs











over a relatively large area. Pattern size will be controlled by varying altitude at which airburst is effected.

Coordination: WADC - Directorate of Air Weapons Systems, WCS . Development Operations Division, WCOES

Holloman Air Development Center, HDOR Air Force Missile Test Center, MTOP Dept. of the Army, Chemical Corps.

Task No. 2 - 50201 (Secret) EW Warhead for E-62 Contractor: Dept. of the Army, Chemical Corps Northrop Aviation Inc.

Object and Nature of Task: The object of this task is to develop a BW (anti-personnel) warnead for the B-62 missile. The warhead will consist of a 7000 lb. cluster of small component BW bombs which cluster will airburst and provide random distribution of component bombs over a relatively large area. Pattern size will be controlled by varying altitude at which airburst is effected. (Collect)

d. Other Information. - The USAF has provided funds to the Army Chemical Corps to establish a project for the development of BW and CW warheads for the B-62. The Bureau of Aeronautics and Bureau of Ordnance of the Dept. of the Navy are listed as having interest in project since information on the BW-CW warhead developments may be useful in their missile and warhead development programs.

The past and proposed AMC funding support to this project is as

follows:

FY:54 FY:55 FY:56 FY:57 FY:58 FY:59 \$180,000 Est. 0 \$110,000 \$210,000 \$1,700,000 \$300,000 \$160,000

These funds will be used to support the service test program and will be expended on items such as unit munitions, cluster adapters and test vehicles.

An information copy of a TWX from Hq. USAF to Hq. ARDC dated 2 July 1953, was received by Wright Air Development Center directing that the requirements for the BW and CW Warheads for the B-62 still exists but that no funds will be available in FY 154 for research and development. (ecret)


e. Background History. - The Army Chemical Corps has been studying the problems associated with designing BW and CW Warheads for the B-62 Missile. This project is unique in that very little is known about the problems of supersonic unit munition delivery or operation. (See Item 21b). (Coords)

f. References: (1) Letter (Classification: Secret) from Deputy Chief of Staff for Development, Headquarters USAF to Commanding General, Air Research and Development Command, Subject (Commune 1),









UNCLASSIFIED

"USAF Guided Missile Warheads and Fuzes (Chemical Corps)" dated 22 March 1951. Wright Air Development Center Control No. 51S-106220.

(2) Statements of Military Characteristics for Biological and GB Warheads for SSM-A-3 (MX 775A) Snark Guided Missile (Secret) from Hq USAF dated 5 June 1951.

(3) TWX from Headquarters USAF to Headquarters Air Research and Development Command Cite AFRD 59902 dated 2 July 1953, WADC Control No. 53WC-33669.

(4) Air Force Guide No. 4 (Classification: Secret) First Edition, Addendum No. 6, 28 May 1953, "Standard Missile Characteristic", B-62, Snark. WADC Control No. 52WC-12086.

(5) Basic letter, (Classification: Secret) from Commanding General, Chemical Corps Research and Engineering Command to Commanding General, Air Research and Development Command, Subject (Condential) "Chemical Warhead Requirements for USAF Guided Missiles" dated 6 November 1952, with: 1st Indorsement from Hq ARDC to Hq WADC dated 18 December 1952, 2nd Indorsement from Hq WADC to Hq ARDC dated 24 February 1953; and inclosures. WADC Control No. 53WC-8087.

REASONS FOR SECURITY CLASSIFICATION: - Since this document reveals intent to obtain offensive capability in BW warfare, it is classified Secret in accordance with policy outlined in letter from Hq USAF (AFOAT) to all major Commands, dated 16 December 1952, Subject: "(Unclassified) Classification Guide for Matters Concerning Biological Warfare and Chemical Warfare".

DOWNGRADING OF SECURITY CLASSIFICATION: - This document shall retain the security classification of Secret until such time as equipment developed under this project has been used in wartime operations for a period of 90 days at which time classification will be reduced to Confidential or until such time as policy expressed in the BW-CW Security Guide mentioned above has been revised.

#### Item 2936

DEPARTMENT OF THE ARMY
OFFICE OF THE CHIEF CHEMICAL OFFICER
Chemical Corps Technical Committee
Army Chemical Center, Maryland

CMINH

17 November 1954

MEMORANDUM FOR RECORD:

SUBJECT: Air Force Project 5066, BW-CW Warheads for B-64 (S)

The attached data sheet for rewritten ARDC Project 5066, same subject as above, is reproduced herewith as information pertinent to related Chemical Corps research and development.

FOR THE CHAIRMAN, CHEMICAL CORPS TECHNICAL COMMITTEE:

T. S. ECKERT

Data Sheet Secy, CCTC
Project 5066

WH5651





Direckson is a

#### Item 2936 Project Data Sheet

1. PROJECT TITLE: BW-CW Warheads for B-64 (Secret)

2. SECURITY CLASSIFICATION: Top Secret

3. PROJECT NUMBER: 5066

5. REPORT DATE: 10 February 1954

- 6. BASIC FIELD OR SUBJECT: Strategic Air Developments, 104A
- 7. SUB FIELD OR SUBJECT: 6 Chemical & Biological Weapons 7a. TECH OBJ.
- 8. COGHIZANT AGENCY: Air Research & Development Command

9. DIRECTING AGENCY: WADC, Armament Laboratory

- 10. REQUESTING AGENCY: Hq, USAF
- 11. PARTICIPATION AND/OR COORDINATION: Dept. of Navy BuOrd, BuAer (I)
  Dept of Army Chemical Corps (P)
- 12. CONTRACTOR AND/OR LABORATORY: Army Chemical Corps; North American Aviation. Inc.
- 13. RELATED PROJECTS: None
- 14. DATE APPROVED: 4 February 1946
- 15. PRIORITY: 1-A
- 17. ESTIMATED COMPLETION DATES: Dev. 1960


Test - 1960

- 18. FISCAL ESTIMATES: FY 51-53 5M; 1954 2M; 1955 12M; 1956 14M; 1957 14M; 58-60 23M; T 70M
- 19. SUPERSEDED REPORTS: This project supersedes Project RDO-R-448-45 in part.
- 20. REQUIFEMENT AND/OR JUSTIFICATION: This project will provide the B-64 missile with a BW-CW capability as expressed in the Statements of Military Characteristics for the Navaho missile warheads, dated 5 October 1951. (See Item 21a.) The authority for this project is contained in a letter (classification: Secret) from Deputy Chief of Staff for Development, Hq USAF, to Commanding General, Air Research and Development Command, Subject: (Confidential) "USAF Guided Missile Warheads and Fuzes (Chemical Corps)", dated 22 March 1951.
  - a. Brief: The performance characteristics as stated in the Military Characteristics for the BW Warhead state that it should be capable of:
    - (1) Effectively dispersing BW munitions in a uniform pattern over as large an area as possible for maximum effectiveness.
    - (2) Achieving a uniform, reproducible ground pattern of unit munitions.
    - (3) All weather employment.

The performance requirements as stated in the Military Characteristics for the CW(GB) Warhead state that it should be capable of:

- (1) Establishing a uniform concentration of GB vapor over an area of approximately 2,700,000 sq. yds. This vapor concentration shall extend from the surface to a height of 6 1/2 feet and shall be lethal to a man at rest within 30 seconds.
- b. Approach: This project is still early in the preliminary study phase and no definite methods of approach have been resolved as yet. One of the major problems that will be encountered in the development of a BW or a CW warhead for the B-64 is that of unit munition separation, dispersion and operation following release at supersonic speeds. Since these problems are common to all supersonic missiles,







HALLASSIFIED

ក់ក្នុង ដូច្នៃ។

altrufili

# Item 2936



### 21.b. Brief of Project and Objective (Continued)

an applied research project will be established to investigate supersonic cluster breakup. The information gained from this research project will expedite both chemical and biological warnead development. It is planned to conduct numerous experimental tests to determine how altitude of cluster breakup affects ground pattern and also to determine if unit munition separation can be accomplished without resorting to the use of separation aids. A comprehensive test program is required since experience and data gained in past development of conventional size horb clusters is of little use in this development program.

C. Tasks:

Task 1. 50205 (BW Warhead for B-64 Contractor: Dept. of the Army, Chemical Corps; North American Aviation, Inc.

Object and Nature of Task: The object of this task is to develop a BW (anti-personnel) warhead for the B-64 missile. The warhead will consist of a 7000-lb cluster of small component BW bombs which will airburst and provide random distribution of component bombs over a relatively large area. Pattern size will be controlled by varying altitude at which airburst is effected. Coordination: WADC -

Directorate of Air Weapons Systems, WCS
Holloman Air Development Center, HDOR
Air Force Missile Test Center, MTOP
Dept. of the Army, Chemical Corps

Task 2. 50204 (Restricted) CW Warhead for B-64
Contractor: Dept of the Army, Chemical Corps; North American Aviation, Inc.

Object and Nature of Task: The object of this task is to develop a CW (GB) warhead for the B-64 missile. The warhead will consist of a 7000-lb cluster of small component GB bombs which cluster will airburst and provide random distribution of component bombs over a relatively large area. Pattern size will be controlled by varying altitude at which airburst is effected.

Coordination: WADC Directorate of Air Veapons Systems, WCS
Development Operations Division, WCOES
Holloman Air Development Center, HDCR
Air Force Missile Test Center, MTOP
Dept of the Army, Chemical Corps

d. Other Information: Reference Box 11 above: The Army Chemical Corps is investigating the BV and CW Warheads for the B-64 with funds provided by the USAF. North American Aviation, Inc. is the missile contractor and will perform the warhead development. The USN BuAer and BuOrd are listed as interested agencies because the developments in the project may be useful to them in connection with the Navy missile and missile warhead development program. An information copy









### Item 2936

### 21.d. Brief of Project and Objective (Continued)

of a TWX from Hq USAF to Hq ARDC, dated 2 July 1953, was received by WADC directing that the requirement for the BW-CW warheads for the B-64 still exists but that no FY 54 funds would be available for research and development. This project is being completely funded by the USAF. No AMC funds have been applied to this project to date. Because this task is in the early phase, no estimate of future AMC funding support can be made at this time. (Secret)

e. Background History: The Army Chemical Corps is studying the feasibility of various methods of achieving a BW and CW capability with this missile. This study is still in an early stage and thus no experimental and developmental work has been initiated.

References:

(1) Letter (classification Secret) from Deputy Chief of Staff for Development, Hq USAF, to Commanding General, Air Research and Development Command, subject (Confidential) "USAF Guided Missile Warheads and Fuzes (Chemical Corps)", dated 22 March 1951. WADC Control No. 518-106220.

(2) Statement of Military Characteristics of Biological Warhead and Chemical (GB) Warhead for SSM-A-4(MX-770) Navaho Missile dated

4 October 1951. WADC Control No. 518-42281.

(3) TWX from Hq USAF to Hq ARDC, cite AFDRD 59902, dated 2 July 1953,

WADC Control No. 53wc-33669.

(4) Letter (classification Secret) from Commanding General, Chemical Corps Research and Engineering Command to Commanding General, Air Research and Development Command, subject (Confidential) "Chemical Warhead Requirements for USAF Guided Missiles," dated 6 November 1952, with : 1st Indorsement from Hq ARDC to Hq WADC dated 18 December 1952; 2nd Indorsement from Hq WADC to Hq ARDC dated 24 February 1953, and inclosures. WADC Control No. 52WC-51541.


Air Force Guide No. 4 (classification Secret) First Edition, Addendum No. 6, 28 May 1953, "Standard Missile Characteristics", B-64, Navaho. WADC Control No. 52WC-12086. (Confidential)

REASON FOR SECURITY CLASSIFICATION:

Since this document reveals intent to obtain offensive capability in Biological Warfare and since information is provided on weapons under development for dissemination of nerve gas GB, it has been classified Secret in accordance with policy expressed in Confidential letter from Hq USAF (AFOAT) to all major commands, dated 16 December 1952, subject: "(Unclassified) Classification Guide for Matters Concerning Biological Warfare and Chemical Warfare." DOWNGRADING OF SECURITY CLASSIFICATION:

This document shall retain the security classification of Secret until such time as equipment developed under this task has been used in wartime operations for a period of 90 days at which time classification will be reduced to Confidential or until such time as policy expressed in the BW CW Security Guide mentioned above has been revised.





SEGDIBITA

Item 2947.

DEPARTMENT OF THE ARMY
OFFICE OF THE CHIEF CHEMICAL OFFICER
Chemical Corps Technical Committee
Army Chemical Center, Maryland

Report "K"
Copy No. \_\_\_\_\_
(19 Pages)

Oh

4-04-15-022 TSE/5190/af 6 Oct 1954

CMLWH-

SUBJECT: Classification of the Clusters, Nonpersistent Gas Bomb, GB, 1000-lb., M34 (ElOlR3) & M34Al (ElOlR5) as Limited Standard and Standard Types, Respectively


TO: Chairman, Chemical Corps Technical Committee

#### References:

- a. Project 4-04-15-05 (S), Munitions (Gas Bomb) for G-Series Filling, established as Project Bl0.5, by CCTC Items 1747 and 1700 22 Jul 47.
- <u>b.</u> CCTC Item 1993 (S), Military Characteristics for a Clusterable G-Series Bomb, 16 Jun 49.
- c. Project 4-04-16-08 (C), 1000-1b. Aimable Cluster Adapter for Incendiary and Chemical Bombs, established as Project Bl2.3c by CWTC Item 1506, 4 Sep 45.
- d. Project 4-04-15-022 (S), 1000-lb. Cluster of GB Bombs, established by CCTC Item 2325, 25 May 51.
- e. Spec MIL-C-11781A, Cluster, Nonpersistent Gas Bomb, 1000-1b., E101R3, 21 Feb 52.
- f. Cml C Drg Cl4-23-1079, Cluster, Nonpersistent Gas Bomb, 1000-1b., El01R3 (w/o Fuze & Wire), 2 Dec 50.
- g. Cml C Drg D14-23-1532, Cluster, Nonpersistent Gas Bomb, 1000-1b., El01R5 (w/o Fuze & Wire), 7 May 54.
- h. Final Engineering Report No. 1; (S), Cluster, Nonpersistent Gas Bomb, 1000-1b., El01R3, 10 Nov 52.
- i. DPGR 122 (S), Cluster Bomb Test, 26 Jan 53.
- j. DPGR 116 (S), One Thousand Pound Cluster Bomb Test,



**(:** 



- $\underline{k}$ . DPGR 137 (CW 7-53) (S), Assessment of a CW Cluster, 8 Dec 53.
- 1. DPGR 144 (CW 1A-54) (S), Operational Suitability Test of a CW Cluster, 9 Feb 54.
- m. Final Report (S), APG/SAS/61-A-1. Operational Suitability Test of the ElOlR3 Cluster Bomb, G8-Filled (S), 5 Mar 54.
- n. Teletype, WCLGW, Wright Air Development Center to CG, A Cml C, Md., 21 May 54.
- o. Letter, CMLRE-E R&E Comd, 21 Jul 54, Standardization of 1000-lb. GB Cluster, to CCmlO, w/2d Ind, CMLRE-E-2, 9 Aug 54, to Chairman, CCTC.
- p. CCTC Item 2677, Procurement of Development Type Items, 14 May 53.
- q. CmlC Mat Comd Instructions 9.2-14(U), Operational Procedure for Use, Storage, Handling, Movement, Decontamination, and Disposal of ElOIR3 Clusters, 18 Feb 54 (as amended).
- r. Letter (C), CMLRE-EA-SS-5b Eng Agcy, 4 Sep 53, Technical Requirements for the Surveillance Inspection of the ElOlR3 Cluster and Separately Packaged Components, thru Cml C R&E Comd to Cml C Mat Comd, w/l Incl.
- s. Interim Surveillance Procedure P-156 (C), Serviceability Determination Procedure for Cluster ElOlR3, 23 Nov 53.
- t. SR 380-5-6 (C), Chemical, Biological, Radiological Warfare Classification, 19 Jun 52.
- u. CCTC Item 2673 (S), Classification Cluster ElOlR3, 1 May 53.
- v. D/F, CMLWO-T OCCmlO, 5 Oct 54, Downgrading of Toxicity Data for GB (Read for Record CCTC Item 2920).

#### 2. <u>Discussion</u>:

a. Development of the G-series agents during World War II by the Germans and the subsequent realization of the potentialities of these gases in modern warfare emphasized the need for urgent development of optimum type munitions for their dispersal. Reference a. identifies the first postwar Chemical Corps project established to undertake such feasibility studies. Although originally concerned with all types of munitions, the work of Project BlO.5 (renumbered 4-04-15-05) was subsequently reoriented with emphasis on development of a suitable bomb for these agents to meet requirements of the Air Force. As a



